



Protection against cold



>> Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all the main works requiring good dexterity in cold conditions.

It is also comfortable as an inner glove with great finesse thanks to the ambidextrous construction. Cold storage, construction, public works, driver, transport, maintenance of green areas, fishing, sports, ski resorts...

>> Technical features

- ✓ Seamless knitted liner. Synthetic fibers.
- ✓ One size only.
- ✓ 13 gauge.
- ✓ Reversible. Elasticated waist.
- ✓ Blue colour.
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.



Learn more: www.singer.fr

>> Advantages

- ✓ ISO 9001 system in production.
- ✓ Seamless knitting: the seamless liner provides exceptional comfort and reduces hand fatigue. There is no roughness. There are no rubbing points (no seams!).
- ✓ The knitting has natural elasticity allowing the glove to fit perfectly around the hand. Elasticated knitted wrist for a snug fit.
- ✓ Can be worn as an insulating liner under other unsupported glove product.
- ✓ Fits either hand, increasing glove life and reducing costs. Reversible design allows replacing one glove at a time, rather than pairs.
- ✓ Special high-tech textile, developed to keep the user dry and comfortable.
- ✓ Textile have qualities of sweetness and lightness, they are easy to care (oleophobic) and dry quickly. (non-hygroscopic).
- ✓ They move perspiration away allowing better thermo-regulation of the body. They also have antibacterial and fungicidal properties.

>> Conformity

This glove has been tested according to the following European standards :


- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Protective gloves against mechanical risks

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	EN 388 : 2016  0 1 2 1 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	0	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	2	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

