



>> Type of use (*)

You can use this product at your work or for your leisure activities, to protect you against the risk of perforation, shock or crushing (**).

Industry, building, fork-lift driver, agriculture, engineering works, receiving, warehousing...

(**) Within the limit of the results of tests made according to the standards in force.

>> Technical features

- ✓ Low cut safety shoe.
- ✓ Upper in leather.
- ✓ Top of upper with polyester lining.
- ✓ Full piece removable footbed.
- ✓ Steel pierce resistant midsole and safety toe cap.
- ✓ Shock absorbing heel.
- ✓ Fastening with D ring and laces.
- ✓ **Colour:** black.
- ✓ **Sizes:** 37 to 47.
- ✓ **Packaging:**
 - Carton of 10 pairs.
 - Each pair individually packed in a box.



Learn more: www.singer.fr

>> Advantages

- ✓ Softness and comfort of leather.
- ✓ Comfortable lining.
- ✓ Very convenient removable insole.
- ✓ Dual-density PU outsole.
- ✓ Energy absorption of heel.
- ✓ Simple but efficient and cost-effective style.

>> Conformity

This product has been tested according to the following European Standard:

- EN ISO 20345: 2011 Personal protective equipment — Safety footwear

It complies with the European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE).

(Category II)

EU type examination certificate (module B) issued by INTERTEK Italia Spa. Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol S1-P	General requirement of the standard EN ISO 20345. Steel toe-protector absorbs an energy of 200 J + closed back, anti-static properties, heel energy absorption. Shoes with pierce resistant midsole up to 1100 newtons.
Slip resistance	Symbol SRC	(= SRA +SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol.

Your distributor **SINGER® SAFETY**

